LIST OF INVENTORS' NAMES AND ADDRESSES

Taminori TOMITA, Sagamihara-shi, JAPAN; Yutaka MIYAZAKI, Sakura-shi, JAPAN.

Title of the Invention A DIGITAL SIGNATURE VERIFICATION APPARATUS

Inventors

Taminori TOMITA,
Yutaka MIYAZAKI.

BACKGROUND OF THE INVENTION

The present invention relates to a technology for verifying digital signatures and in particular to a technology which is capable of displaying data upon 5 which at least one digital signature is put.

As to documents such as contracts which are made among entities such as government offices and privately-owned corporations, exchanging of electronic documents which are prepared by using information

10 processing devices such as computers has been increased in lieu of exchanging paper documents. On exchanging of electronic documents, electronic signatures (digital signatures) have been used for authentication of person identification or protection against tampering by

15 unauthorized persons. The technology of the digital signature per se is described in, for example, "Digital signature and encryption technology", par. 4.3 "digital signature", Piason Education (1997).

Various digital signature such as multiple20 signature in which a digital signature is further put
on digitally signed data, and partial signature is
which digital signature is put on only a specified
portion of the data have been proposed. It is possible
to put a plurality of digital signatures by utilizing
25 these schemes.

A method of representing the fact that data is digitally signed includes an Authenticode technique which is described in, for example, "Web security and commerce" par. 9.2 "Authenticode technique of

- 5 Microsoft" to par. 9.4 "other code signature method",
 1998, O'Reilly Japan, Co. Ltd. This technology is
 adapted to display a certificate when it detects a
 signature. A technology to represent the state of
 multiplesignature includes a multiple-signature
 10 apparatus as is disclosed in JF-A-2000-293102 entitled
 - The correspondence relationship between digital signature and data to be digitally signed has

"Digital multiple-signature apparatus and recording

SUMMARY OF THE INVENTION

15 not heretofore been considered.

medium".

Since the correspondence relationship has not been considered as mentioned above, in the prior art, only the file name is displayed as information on the 20 data signed, when the fact that the data is digitally signed is displayed. Accordingly, there is a problem that the content of the data signed digitally can not be readily confirmed.

And, XML (Extensible Markup Language)

25 documents, which have recently attracted attention, is
possible to put a partial signature which specifies a
part of file as a signature object. However, it is

difficult for the above-mentioned prior art which assumes to put digital signature on the whole of the file, to immediately confirm the partial signature and the content of the signature object data.

It is an object of the present invention to 5 readily confirm the digital signature and the content of its signature object data (file).

In order to accomplish the above-mentioned object, the present invention has features as follows:

The data which is an object of the digital signature is related with the information representative of the range of the object of the digital signature involved. The data which is an object of the digital signature may be a partial data 15 in a predetermined unit. An example of the predetermined unit may be one file.

The present invention also has features as follows: A digital signature object data identifier is annexed to a digital signature file as an information 20 which represents the range of the digital signature object. The range of the digital signature object (partial data) is detected based upon the digital signature object data identifier which is attached to the entered digital signature file. Detecting the 25 range of the digital signature object includes detecting what data is included in the digital signature file by analyzing the digital signature file.

The present invention further includes

correlation of the content of the range of the digital signature object with the data related with the digital signature and displaying it. The data which is related with the digital signature includes information on an apparatus or user that has put the digital signature. Displaying with correlation includes displaying on the same display.

BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 is a view showing a digital signature

 10 data dsign.xml which is displayed by the digital

 signature display system of one embodiment of the

 present invention;
- Fig. 2 is a schematic diagram showing the digital signature display system of the embodiment of the present invention;
 - Fig. 3 is a flow chart showing the processing procedure of the digital signature analyzing and processing unit 210 of the present embodiment of the present invention;
- Fig. 4 is a flow chart showing a process of the digital signature display image generating and processing unit 211 of the embodiment of the present invention:
- Fig. 5 is a diagram showing the digital 25 signature data dsign.xml;
 - Fig. 6 is a diagram showing an example of the digital signature information which is obtained by

processing the digital signature data dsign.xml in the digital signature analyzing and processing unit 210;

Fig. 7 is a view showing an example of the display of the digital signature data dsign.xml;

Fig. 8 is a view showing an example of the display of the digital signature data dsign.xml, which is added with a frame representing the data which is represented by an identifier ALL;

Fig. 9 is a diagram showing the digital 10 signature data dsign2.xml;

Fig. 10 is a diagram showing an example of the digital signature information which is obtained by processing the digital signature data dsign2.xml in the digital signature analyzing and processing unit 210;

15 Fig. 11 is a view showing the digital signature data dsign2.xml which is displayed by the digital signature display system of the embodiment of the present invention;

Fig. 12 is a diagram showing the digital 20 signature data dsign3.xml;

Fig. 13 is a diagram showing an example of the digital signature information which is obtained by processing the digital signature data dsign3.xml in the digital signature analyzing and processing unit 210;

25 and

Fig. 14 is a view showing the digital signature data dsign3.xml which is displayed by the digital signature display system of the embodiment of

the present invention.

DESCRIPTION OF THE EMBODIMENTS

Now, a digital signature display apparatus of an embodiment for displaying the digital signature will be described.

Fig. 2 is a diagram showing the schematic structure of the digital signature display apparatus of the present embodiment. As shown in Fig. 2, the digital signature display apparatus of the present embodiment comprises a CPU 201, memory 202, magnetic disc unit 203, entry unit 204, display unit 205 and a network connection unit 206.

The CPU 201 controls an operation and a processing of the whole of the digital signature

15 display apparatus. The memory 202 is a storage for loading therein various processing programs and data to control the operation of the whole of the digital signature display apparatus.

The magnetic disc unit 203 is a storage to
20 store the above-mentioned various processing programs
and data. The entry unit 204 inputs operator guidance
and the like to the digital signature display
apparatus. The display unit 205 displays states of the
operation of the digital signature display unit and the
25 states of digital signature. The network connection
unit 206 connects the digital signature display
apparatus to the network to receive and transmit data

from and to the other devices which are connected to the network.

The digital signature display apparatus further comprises a digital signature analyzing and 5 processing unit 210 and a digital signature display image generating and processing unit 211.

The digital signature analyzing and processing unit 210 is a processing unit for inputting a digital signature file designated by the entry unit 10 204, verifying the data signed digitally and the validity of the digital signature, analyzing informations of a digital signatory and outputting a result of the analysis.

The digital signature display image

15 generating and processing unit 211 is a processing unit for inputting the analysis result output from the digital signature analyzing and processing unit 210, generating a digital signature display image and displaying the image on the display unit 205.

20 It is supposed that the program which causes the digital signature display system to operate as the digital signature analyzing and processing unit 210 and the digital signature display image generating and processing unit 211 is loaded on the memory and 25 executed, after recorded on a recording medium such as CD-ROM and the like. The recording medium for recording the program may be any recording media other than CD-ROM. Alternatively, the program may be

distributed over the network.

The digital signature may be conducted according to a specification, for example, XML-signature which are being defined by W3C, a standard organization. An example of dsign. xml of the digital signature file which conforms with XML is illustrated in Fig. 5. The present digital signature file represents digital signature information between tag <signature> in line 002 to </signature> in line 023. A signature object data identifier 501 "ALL" designated in the tag <Reference> in line 005 is an identification which identifies the signature object data. The data represented by said identifier 501 "ALL" is enclosed by the tags <Object id="All" in line 024 to </Object> in line 046 in the present digital signature file.

Fig. 3 is a flow chart showing the process of the digital signature analyzing and processing unit 210 of the digital signature display apparatus of the present embodiment. As shown in Fig. 3, the digital 20 signature analyzing and processing unit 210 receives the digital signature file name entered from the entry unit 204 and analyzes the digital signature.

Now, the processing will be described by way of the case in which the digital signature file 25 dsign.xml shown in Fig. 5 is designated.

At step 301, the designated digital signature file dsign.xml shown in Fig. 5 is read from the magnetic disc unit 203, and the digital signature is

2.5

retrieved from the file. In the present embodiment, the presence of the digital signature is recognized by retrieving the data enclosed between the tags <Signature> and </Signature>.

At step 302, if there is no digital signature in the designated digital signature file, or only digital signatures already analyzed therein, then the processing is terminated. If a digital signature not analyzed is detected, the program sequence proceeds to 10 step 303.

At step 303, the detected digital signature is analyzed to retrieve the digital signature object data. In the digital signature file in Fig. 5, the data represented by the digital signature object data 15 identifier "All" in the tag <Reference IDREF="ALL"> in line 004 is retrieved. As a result of the retrieval, it is recognized that the data from <Object ID="ALL> in line 023 to </Object> in line 047 in the digital signature file is the signature object data. The term 20 "identifier" used herein is data which identifies the particular data. The data identified by the identifier may be external of the digital signature file. In this case, the digital signature object data identifier is represented in, for example, URI form.

The file which includes the digital signature object data is hereinafter referred to as "digital signature data file".

At step 304, verification of the digital

signature is performed to determined whether or not the digital signature is true, and an information on the signatory is obtained. In the digital signature file dsign.xml in Fig. 5, the information on the signatory is described in a portion "CN=Tomita Taminori, O=Hitachi, C=JP" between the tags <X509Name> and </X509Name> in line 017.

At step 305, the field of the digital signature object data established at step 303, the 10 digital signature object data file name, the signatory obtained at step 304 and the result of the signature verification are output as a digital signature analysis result.

An example of the digital signature analysis

15 result is shown in Fig. 6. The result comprises the
digital signature file name, signatory information,
digital signature object data file name, signature
object data identifier and the signature verification
result.

20 After outputting the digital signature analysis result, the program sequence returns to step 302 again. If there is unanalyzed digital signature, steps 303 to 304 are repeated. When the analysis of the digital signature existing in the digital signature 25 file is completed, then processing is terminated. The processing may be terminated subject to a completion of analysis of all target digital signatures.

After termination of the processing of the

digital signature analyzing and processing unit 210, processing in the digital signature display image generating and processing unit 211 is initiated. As shown in Fig. 4, the digital signature display image 5 generating and processing unit 211 inputs the digital signature analysis result from the digital signature analyzing and processing unit 210 and generates an image representing the digital signature object.

At step 401, the digital signature analysis

10 result from the digital signature analyzing and
processing unit is input.

At step 402, if undisplayed digital signature analysis result is not in the digital signature analysis result, the processing is terminated. When an undisplayed digital signature exists, the program sequence will proceed to step 403.

At step 403, the digital signature object data file shown in the undisplayed digital signature analysis result is displayed. When the digital signature object data file is already displayed, the processing is omitted. An example of the display of the digital signature object data file dsign.xml in case of Fig. 6 is shown in Fig. 7.

At step 404, a frame, which represents the
25 field of the digital signature object data among the
digital signature object data file displayed at step
403, is generated. A display example in case of Fig. 6
is shown in Fig. 8. A reference numeral 101 denotes

the frame which represents the field of the digital signature object data.

At step 405, a result of the digital signature analysis, which is represented by the frame indicating the field of the digital signature object data displayed at step 404, is displayed. An example of the display in case of Fig. 6 is shown in Fig. 1. Reference numerals 101 and 102 denote the frame representing the field of the digital signature object data and the digital signature analysis result represented by the frame 101, respectively.

The signature analysis result may be displayed by colors or symbols other than character array as shown in Fig. 1.

15 Alternatively, the signature verification result may be represented by, for example, the color of the display frame 101.

After completion of step 405, the program sequence will returns to step 402 again. If

20 undisplayed digital signature analysis result exists, then steps 403 to 405 are repeated. When generation of the image of the digital signature analysis result is completed, the processing is terminated. The processing may be terminated subject to a completion of the generation of all of the images of the digital signature analysis results.

As described above, in the digital signature display apparatus of the present embodiment, it is

possible to confirm what contents are digitally signed by whom without requiring a number of operations to display the information on the signatory and the data content of the signature object on a screen.

Although the digital signature analyzing and processing unit 210 and the digital signature display image generating and processing unit 211 are implemented in all-in-one device in present embodiment, they may be implemented by discrete devices.

Fig. 9 shows an example of second digital signature file dsign 2. xml which is described in XML.

The second digital signature file comprises a first digital signature 901 of tag <Signature> in line 002 to tag </signature> in line 023 and a second digital signature 903 in lines 024 to 045.

A tag signature object data identifier 902 in Fig. 9 identifies the signature object data of the first digital signature 901. The identifier 902 is designated in the tag <Reference>. The data

20 represented by the identifier 902 is enclosed between the tags <Object Id="author"> in line 033 in the file dsign.xml in Fig. 5. A specific example of the identifier 902 may be "http://home/dsign.htm#author".

Similarly, the signature object identifier
25 904 in Fig. 9 is an identifier for identifying the
signature object data of the second digital signature
903. The data represented by the signature object
identifier 904 is the location enclosed between a tag

<Object Id="title"> in the line 034 and the tag
/Object> in the line 045 in the file dsign.xml in Fig.
5. A detailed example of the signature object
identifier 904 may be "http://home/dsign.html#title".

A result which is obtained by processing such a second digital signature file in said digital signature analyzing and processing unit 210 is shown in Fig. 10.

Fig. 10 shows a result of the digital

10 signature analyzing of the second digital signature
file. Reference numeral 1001 in the drawing denotes a
result of digital signature analysis of the first
digital signatures 901, and reference numeral 1002 in
the drawing denotes a result of digital signature

15 analysis of the second digital signatures 903.

Subsequently, a digital signature display image is generated by processing the result of the digital signature analysis shown in Fig. 10 in the digital signature display image generating and processing unit 211.

An example of the displayed image of the second digital signature file is shown in Fig. 11. A display frame 1101 denotes the range of the signature object of the first digital signature 901. Signature 25 information 1102 is the information relating to the signature analyzing result of the first digital signature 901. Similarly, a display frame 1103 denotes the range of the signature object of the second digital

signature 903 and signature information 1104 is information relating to the signature analyzing result of the second digital signature 903.

As described above, in the digital signature

5 display apparatus of the present embodiment, it is
possible to confirm what content is digitally signed by
whom without requiring a number of operations to
display the content of the digital signature object
file, the field of the digital signature object and the

10 information on the digital signatury on one screen even
if the data of the digital signature object is part of
the file. It is also possible to do so if one
signature object file is signed by a plurality of
signatories.

Fig. 12 shows an example of a third digital signature file dsign3.xml which is described in XML.

The third digital signature file comprises
the first digital signature 1201 in lines 002 to 018
and the second digital signature 1203 in lines 020 to
20 036.

The signature object data of the first digital signature 1201 is a field 1202 represented by an identifier "ALL" in lines 019 to 049. Similarly, the data which is the object of verification of the second digital signature 1203 is a field 1204 represented by an identifier "title" in lines 037 to 048.

A result obtained by processing the third

digital signature file in the digital signature analyzing and processing unit 210 is shown in Fig. 13.

Fig. 13 shows the result of the digital signature analysis of the third digital signature file.

5 Reference numeral 1301 in the drawing denotes a result of digital signature analysis of the first digital signatures 1201, and reference numeral 1302 in the drawing denotes a result of digital signature analysis of the second digital signatures 1203.

Subsequently, a digital signature display image is generated by processing the result of the digital signature analysis shown in Fig. 13 in the digital signature display image generating and processing unit 211.

An example of the displayed image of the third digital signature file is shown in Fig. 14. A display frame 1401 denotes the range of the signature object of the first digital signature 1201. Signature information 1402 is the information relating to the signature analyzing result of the first digital signature 1201. Similarly, a display frame 1403 denotes the range of the signature object of the second digital signature 1203 and signature information 1404 is information relating to the signature analyzing result of the second digital signature 903.

It can readily be confirmed from the relation of inclusion of the display frames 1401 and 1403 that the first digital signature 1201 is the signature for

the field represented by the identifier "title" and the data including the second digital signature 1203.

As described above, according to the digital signature display apparatus of the present embodiment, 5 it is possible to confirm what content is digitally signed by whom based upon the relationship of inclusion of the fields of the digital signature objects even if the data of the digital signature object is signed by a plurality of digital signatories.

A way of displaying the field of the signature object data in accordance with the present invention is not limited to the above-mentioned embodiments. For example, it may be displayed by displaying the changed color of the screen background 15 in lieu of frame line in the embodiments.

The content of the display of the signature information in accordance with the present invention is not limited to the above-mentioned embodiments. For example, the information on the signatory and the 20 signature verification result of the embodiment may be displayed.

The signature verification result may be displayed. The signature verification result may be separately displayed.

25 The method of digital signature in accordance with the present invention is not limited to the abovementioned embodiments. The present invention is applicable to another method of digital signature

including at least the signature object data and information specifying the information on the signatory.

In other words, the present invention may be 5 embodied without departing from the gist that the content of the file including digitally signed data, the field of the digital signature object and the signature information is displayed in means for representing the digital signature.

Since the content of the file including the data of the digital signature object is displayed and the field of the digital signature object and the digital signature information is two-dimensionally superposed thereon in accordance with the present embodiment, it is possible to confirm the relationship among various digital signatures such as partial or multiple signatures without necessity of a number of operations.

In accordance with the present invention, it 20 is possible to readily note the content of the data which is to be digitally signed.